

Л.ВАНГАНЫ НЭРЭМЖИТ ЗАВХАН АЙМГИЙН ХӨГЖИМТ ЖҮЖГИЙН ТЕАТРЫН ТАВИЛГА, ТЕХНИК ХЭРЭГСЭЛ
ТОНОГ ТӨХӨӨРӨМЖИЙН ТЕХНИКИЙН ТОДОРХОЙЛОЛТ

№	Тодорхойлолт	Хэмжих нэгж	Тоо ширхэг	Үзүүлэлт	Брэнд
1	Чанга яригч	ш	16	<p>*Nominal Impedance: 8 Ohms Power Capacity: Continuous / Program / Peak: Passive : 800W / 1600 W / 3200 Wbi-amp LF: 800W /1600W 3200 Wbi-amp HF:75W /150W/ 300/ *Frequency Range: 43 Hz-20 kHz (-10 dB) 9 * Maximum SPL:131 dB SPL peakL.F 134 dB SPL cont avg (140 dB peak) H.F 133 dB SPL cont avg (139 dB peak) Passive mode: 134 dB SPL cont avg (140 dB peak) * System Sensitivity: Passive Mode 96 dB SPL (1 watt @ 1 meter) * Crossover Freq. : 1.2kHz</p>	JBL SRX715 /дүйцхүйц/
2	нам яригч	ш	8	<p>*Nominal Impedance: 8Ohms * Power Capacity: Continuous / Program / Peak: Passive: 800W / 1600W/ 3200W *Frequency Range: 31 Hz-220 Hz (-10 dB) * Maximum SPL :130 dB SPL peak (1 watt @1 meter) *System Sensitivity: Passive Mode 95 dB SPL (1 watt @ 1meter) * Crossover Freq. : 30 Hz, 24 dB/ octave HPF80 Hz, 24 dB/ octave LPF</p>	JBL SRX718S /дүйцхүйц/
3	Чадлын өсгөгч	ш	8	<p>* In 4Ω bridged mode the 3200 watts * Yamaha #039;s exclusive EEEngine technology significantly reduces power consumption and heat generation.</p>	Yamaha P700S /дүйцхүйц/
4	Пульт	ш	1	<p>24 Input channels (16 Mic inputs, 4 Stereo line inputs, 16 insert I/O) Dual SPX Digital Effects Versatile EQ for Effective Sound ShapingSix Aux Sends & amp; Two Stereo Aux Returns 14 Buses In All For Flexible Signal Routing</p>	Yamaha MG24/14FX /дүйцхүйц/
5	Монитор яригч	ш	4	<p>*300 watt passive system with 1200 watt peak power rating * 90(H) x 50(V) waveguide for uniform audience coverage * Includes monitor angle and dual angle 35mm pole socket *Includes M10 suspension points for easy rigging and available in white</p>	JBL PRX412M /дүйцхүйц/
6	Монитор яригчны чадлын өсгөгч	ш	2	<p>*In 4Ω bridged mode the 2000 watts * Yamaha #039;s exclusive EEEngine technology significantly reduces power consumption and heat generation.</p>	Yamaha P3500S /дүйцхүйц/

7	Зурвас хувиарлагч	ш	1	Analog Inputs- Number of Inputs:(2) Line inputs. (1) RTA Mic input Connectors:(2) Female XLR line inputs, XLR RTA Mic input Response:20Hz- 20kHz, +/-0.5dB Interchannel Crosstalk :<-110 dB, -120dB typical Crosstalk input to output<-100 dB POWER SUPPLY- Operating Voltage 100-120VAC 50/60 Hz - EU:220-240 VAC 50/60 Hz Power Requirements25 W	DBX DBX/PA /дүйцхүйц
8	Эквалайзер	ш	1	Freequency response 20Hz to 20kHz+0.5dB,-0.5dB (@+4dB 600ohms) Total harmonic distortion Less than 0.05% (@+4dB 600ohms EQ=FLAT) Hum & noise level -96dB (EQ=ALL FLAT INPUT MAX) Center frequency 20Hz to 20kHz (1/3 oct 31 band)Level control +/-12dB +/-9dB (selectable) Filter HPF =-12dB/oct 20Hz to 200Hz variable Power requirement AC100V, 50/60HzAC120V, 60HzAC230V, 50HzPower consumption 20W	Yamaha Q2031B /дүйцхүйц/
9	Угастай микрофон	ш	4	Type: DynamicFrequency Response 50 to 15,000 HzPolar Pattern: CardioidSensitivity (at 1,000 Hz Open Circuit Voltage) : -54.5 dBV/Pa (1.85 mV)1 Pg=94 dB SPLImpedance: Rated impedance is 1500 (300Ω actual) for connection to microphone: inputs rated low impedanceConnector: Three-pin professional audio connector (male XLR type)	Shure SM58LC /дүйцхүйц
10	Зайны 1 гартай микрофон	ш	2	Audio Output Level (ref. +/-38 kHz deviation with 1 kHz tone) XLR connector (into 600 Ohm load):-13 dBV 1/4 inch connector (into 3000 Ohm load):-2 dBV Output Impedance XLR connector: 200 Ohms 1/4 inch connector: 1 kilohm Impedance balanced Sensitivity- 105 dBm for 12 dB SINAD, typical Image Rejection >70 dB, typical Power Requirements	Shure SLX24E/Beta 58A/дүйцхүйц
11	Микрофоны хөл	ш	8	Three-way Adjustable Boom Arm * Stable Tripod Base * Quick-release Clutch	Ultimate JS-MCFB100C/дүйцхүйц
12	Мульти кабель	ш	1		Climb SMT32/OSC 50/ дүйцхүйц
13	чихээвчний микрофон	ш	5	The rugged PGXD 1 bodypack transmitter easily clips onto a belt or guitar strap, and provides you with a 20Hz-20kHz frequency range. The PGXD4 receiver offers 24-bit/48kHz accurate sound	Yamaha Shure PGXD 14/ BETA 98H-XB/дүйцхүйц/

14	хөгжимний микрофон	ш	6	Element: Electret Condenser Polar Pattern: Cardioid Frequency Response: 30Hz ~16.000 Hz Sensitivity: -48 dB +/-3 dB Impedance: 800 ohm Operating Voltage: 1.5V -10V D.C or 48 V Phantom Power Mounting: Clip Cord Long: 9Ft Weight:2 oz (not including connector)	Yamaha Av-JEFES PMM 19B-SH4-PA Piano /дүүцхүйц/
15	Албаны зориулалт бүхий хүрэн арьсан буйдан, крисло /VIP өрөөнд/	ком	2	Улаан хүрэн өнгийн сайжруулсан хиймэл савхин бүрээстэй	626 Three seat, PU sofa w/wooden leg
16	Албаны зориулалт бүхий хүрэн бичиг хэргийн шүүгээ /VIP өрөөнд/	ш	3	шүүгээний дээд хэсэг шилэн хаалгатай, доод хэсэг цоожтой цэвэр модон материалтай, хаалгатай Хэмжээ: 900L*400W*250H мм	CM-BS205290-R Book shelf
17	Албаны зориулалт бүхий бичгийн ширээ /захиргааны ажилчдад/ 1200x600x420	ш	3	цэвэр модон, өнгө нь хүрэн байх	
18	LED TV үүдний вестибюльд	ш	1	65 инч 4K HDR 3D Andriod Smart 16:9 800Hz	
19	Гадна тайзны 8000x6000	ком	1	хөнгөн цагаан төмөр каркас, 1 м өндөртэй цэвэр модон шал, 2 талын жижиг туслах шат	
20	кондинсатор /зүүдэг микрофон/	ш	2	Element: Electret Condenser Polar Pattern: Cardioid Frequency Response: 30Hz ~16.000 Hz Sensitivity: -48 dB +/-3 dB Impedance: 800 ohm Operating Voltage: 1.5V -10V D.C or 48 V Phantom Power Mounting: Clip Cord Long: 9Ft Weight:2 oz (not including connector)	

АЙМГИЙН ЗАСАГ ДАРГЫН ТАМГЫН ГАЗРЫН ХӨРӨНГӨ ОРУУЛАЛТ ХӨГЖЛИЙН БОДЛОГО ТӨЛӨВЛӨЛТИЙН ХЭЛТЭС