

БАТЛАВ:



ЗДТГ-ЫН ДАРГА

А.МӨНХТУУЛ

БАЯНЧАНДМАНЬ СУМЫГ БҮРЭН КАМЕРЖУУЛАХ ТЕХНИКИЙН ТОДОРХОЙЛОЛТ

ТТГ-А-1942

№	Худалдан авах бараа	Техникийн тодорхойлолт	Тоо ширхэг	Хэмжих нэгж	зураг
1	Гадаа хяналтын камер Bullet Camera H.265+ 4MP 3,6mm Aikvision-дүйцэх	Image Sensor 1/1.8" Progressive Scan CMOS Min. Illumination 0.0014 @ F1.0 (1/30 s, AGC ON), 0.002 @ F1.2 (1/30 s, AGC ON), 0 Lux with LED on Shutter Speed 1/3 s to 1/100,000 s Slow Shutter Yes Focal length 4/6 mm H.265 Type Main Profile H.265+ Main stream supports Video Bit Rate 32 Kbps to 8 Mbps Network Storage , IP address filter Firmware Version V5.5.53 Operating Conditions -30 °C to +60 °C (-22 °F to +140 °F), humidity 95% or less (non-condensing) Power Supply PoE (802.3af, class 3) Power Consumption 12 VDC, 0.5 A, max: 6 W PoE: (802.3af, 36 V to 57 V), 0.3 A to 0.1 A, max: 7.5 W Visible Light Range Warm white LEDs (3000K), up to 30m Protection Level IP67	33	ш	
2	Network IR PTZ Camera with Hikvision-дүйцэх	MP 25× Network IR Speed Dome adopts 1/2.8" progressive scan CMOS chip. With the 25× optical zoom lens, Up to 5 faces captured at the same time □ 1/2.8" progressive scan CMOS □ High quality imaging with 4 MP resolution □ Excellent low-light performance with powered-by-DarkFighter technology □ 25× optical zoom and 16× digital zoom provide close up views over expansive areas □ Expansive night view with up to 100 m IR distance □ Support H.265+/H.265 video compression Movement Range (Pan) 360° , Operating Condition -30 °C to 65 °C (-22 °F to 149 °F). Humidity 90% or less	7	ш	Hikvision-дүйцэх
3	64 сувгийн бичигч тохооромж	P HDD hot swap with RAID0, RAID1, RAID5, RAID6 and RAID10 storage scheme configurable Video Input and Transmission Up to 64-ch 12 MP IP cameras can be connected Connectable to the third-party network cameras Compression and Recording H.265+ compression	1	ш	

		effectively reduces the storage space and costs by up to Full channel recording at up to 12MP resolution HD Video Output HDMI1/VGA1 and HDMI2/VGA2 outputs provided HDMI1 Video output at up to 4K (3840 × 2160) resolution Storage and Playback Up to 8 SATA interfaces and 1 eSATA interface connectable for recording and backup Smart search for efficient playback. 8/16-ch synchronous playback at up to 1080p resolution Smart &POS Function Ethernet Access 2 Gigabit Ethernet network interfaces;		
4	Нikvision- дүйцэх	дугаар танигч камер Nikvision 4MP DeepinView ANPR Moto Varifocal IDS-2CD7A46G0/P-IZHSY дүйцэх	2	ш
5	Нikvision- дүйцэх	LED 65" 4K HDMI оролттой камерт зориулагдсан ханад тогтоох суурьтай	1	ш
6	Хярд диск seagate	Хяналтын камерийн бичигчинд суурилах тасралтгүй ажиллах зориулалтай 8TB sata 3.5"	4	ш
7	Утасгүй сүлжээний антена	5 ghz давтамжтай ubiquiet power beam M5 антенагай дүйцэх	2	ш
8	Пое свич	8-Port PoE Switch (Unmanaged) Ethernet Port 1*1000 Base-X 1*10/100/1000 Base-T 8*10/100 Base-T (PoE power supply) PoE Power Consumption Each power ≤30W, Total≤96W Working Temperature-30°C~65°C Two-layer industrial PoE switch MAC auto study and aging, MAC address list capacity is 8K Support IEEE802.3af, IEEE802.3at standard	12	ш
9	16A автомат	220V	12	ш
10	Тоолуур	220вольт баталгаажсан	12	ш

11	Модуль	1000Base-BX WDM Bi-Directional SFP Module, LC, SM, 20km	24	ш
12	Жампер кабель	Jumper SC-SC 1m SM Simplex	24	ш
13	хамгаалалтын хайрцаг	ус чийгний хамгаалалттай. төмрийн зузаан 1мм , зэвэрдэггүй зориулалтын цоожтой 400*500*200 харьцаагай	11	ш
14	камерийн шон	8м хүргэл уртай газарт 1,5м хүргэл суулгах	12	ш
15	switch manage	Architecture ARM 32bit CPU 98DX3236 CPU core count 1 CPU nominal frequency 800 MHz Switch chip model 98DX3236 Dimensions 443 x 194 x 44 mm RouterOS license 5 Operating System RouterOS / SwitchOS Size of RAM 512 MB Storage size 16 MB Storage type FLASH MTBF Approximately 200'000 hours at 25C Tested ambient temperature -20°C to 60°C , SFP ports 12, Ethernet Combo ports 4	1	ш
16	UTP Cat6		2	6
17	12 core шилэн кабель	Агаарын	11000	м

18	шилэн кабелийн бэхэлгээ	төмөр	500	ш	
19	toten 12U rack		1	ш	
20	ракны гавиур		2	ш	
21	PDU залгуур	Сайн чанартай	1	ш	
22	cable management		1	ш	
23	fdf 24 core		1	ш	
24	fdf 4 core		12	ш	
25	муфть	солонгос	8	ш	
26	гј45 cat6		2	х	
27	цуглуулгын хрон төмөр- гадаа зориулагдсан		40	ш	
28	хар хоолой 24Ф		2	б	
29	2*2.5 цахилгааны кабель	Гадаа	400	м	
30	Тог баригч	2000VA/1200W UPS	1	ш	
31	Сиф кабель	Гадаа кабель	300 м	м	

ТЕХНИКИЙН ТОДОРХОЙЛОЛТ БОЛОВСРУУЛСАН: *Дамсүрэн*. Х.БАТДОРЖ

ТЕХНИКИЙН ТОДОРХОЙЛОЛТ ХЯНАСАН: ЗАСАГ ДАРГЫН ОРЛОГЧ *Ц.Энхболд* Ц.ЭНХБОЛД

Untitled Map
Write a description for your map.

Legend

- Feature 1
- Untitled Path



1000 ft